



152 Rollins Avenue #102 Rockville, MD 20852
800-762-9010 240-780-3309 (f)
<http://www.waterhogfloormats.com>

Waterhog Premier Mats

Specifications

General Information:

Surface

Fiber Type: Solution Dyed Polypropylene, outstanding lightfastness
Weight: 36 ozs/sqyd
Nub Height: 3/8"
Design: Diamond Pattern

Backing

Type: 100% SBR Rubber (20% Recycled Content)
Thickness: 0.110" – Border; 0.190" Nubs; 0.050" – Between Nubs
Durometer: 60

Features:

- Reinforced face NUBS: Face NUBS are reinforced with rubber to resist crushing, maintaining high performance and extending product life.
- "Water Dam" border: Border is designed to hold water and dirt on mat keeping them off carpets and floors. Unique raised rubber border allows Waterhog mats to hold up to 1 1/2 gallons of water per square yard. Some styles available without dam for outside use, so water can drain easily.
- Raised NUB surface: Removes and traps dirt and moisture and holds it on mat below shoe level so it is not tracked in.
- TriGrip backing: Gripping action minimizes movement on most carpets and improves traction on hard surfaces.
- Rubber backing: Lays flat, won't crack or curl like vinyl mats.
- Indoor/Outdoor: Durable anti-static polypropylene face suitable for indoor or outdoor use.
- Polypropylene fiber system dries quickly preventing fading and rotting.
- Easy to clean: Just vacuum or hose off and hang to dry.
- Colorfast: Solution dyed for excellent light and wet fastness.
- Not adversely effected by salt or ice melt.
- Should not be used in areas exposed to animal fats (kitchens) or petroleum products.
- Passes Flammability Standard DOC-FF-1-70
- Anti-static: Waterhog mats have a maximum average voltage of 1.6 KV as measured by the AATCC 134 Electrostatic Propensity Test and meets IBM's minimum standard for electrical resistance (NFPA99). Waterhog mats are safe for use in computer rooms and around electronic equipment.
- ASTM C 1028-89 Static Coefficient of Friction Dry .70